

MASKCOAT LLC

1500A TIM STREET
WEST MONROE, LOUISIANA 71292
888-218-7227



Fax (318) 812-0088
info@maskcoat.com
www.maskcoat.com

PROCOAT TECHNICAL DATA SHEET

PROCOAT

GENERAL PURPOSE STOP-OFF LACQUER/MASKANT

PROCOAT is a fast air dry general purpose solvent stop-off lacquer or liquid maskant that can be applied by brush, dip or spray to the surface to be masked. Use PROCOAT STRIPPER/REDUCER to thin to spray viscosity. Under normal ambient conditions parts may then enter the plating cycle within 30-45 minutes depending on the thickness of the wet film applied. After minimal drying of the final process rinse PROCOAT is removed in minutes using PROCOAT STRIPPER/REDUCER.

PROCOAT is transparent red in color to enable easy determination of application location, detection of inadvertent application, and completeness of removal. The light coloration allows some visual determination of both wet and dry film thickness.

PROCOAT with a 45-50 sec. #2 Zahn Cup viscosity enables speed in application and removal.

Depending on plating process requirements, more than one coat of PROCOAT may be applied after adequate solvent flash off. Cure may be accelerated by increasing ambient temperature.

PROCOAT contains flammable solvents and is available in 1 gal., 5 gal., and 55 gal containers.

SEE THE REVERSE SIDE FOR PRECAUTIONS AND WARRANTY

PRECAUTIONARY INFORMATION

CONTAINS FLAMMABLE LIQUID

CONTAINS VOLATILE SOLVENTS-Keep away from open flames, sparks and all sources of potential ignition at all times. Maintain adequate ventilation in all areas. Always wear adequate appropriate protective clothing, breathing and eye protective equipment. Store at temperatures between 32 degrees F and 105 degrees F. Keep all containers closed when not in use. Avoid repeated or prolonged breathing of vapors. Observe all OSHA, EPA, and all other Federal, State, and local regulations when using this product. Prolonged contact of liquid material with the skin may cause irritation. In case of eye contact, flush eyes thoroughly for at least 15 minutes with water and consult a physician. Always consult the Material Safety Data Sheet prior to usage for additional warnings and information.

EMERGENCY TELEPHONE NUMBER

1-318-812-0089

WARRANTY DISCLAIMER

Based on the Seller's experience, the information contained herein is believed to be accurate and reliable. Users are requested to evaluate this product prior to use to determine the suitability for their particular application.

Seller disclaims any express warranties and nothing herein shall constitute any warranty, whether express or implied, and Seller hereby DISCLAIMS ALL WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Seller warrants only that its product will meet those specifications designated as such herein. The EXCLUSIVE REMEDY for all proven claims whether through negligence, strict liability, tort or otherwise is limited to an amount equal to the price of the particular products or services giving rise to the liability, or, at the election of the Seller, the replacement of the product in question. In no event shall Seller be liable to Purchaser for any incidental, consequential, indirect, or special damages, including without limitation, lost revenues or profits, even if Seller was advised of the possibility of such lost revenues or profits. Unless otherwise noted, Seller warrants for a period of one year from the date of manufacture that all products delivered to the customer shall be free from defects. All warranty claims with respect to any alleged defect must be received by the Seller within one year after the manufacture of the goods. Upon timely receipt of verified claims, Seller, at Seller's option, will replace or refund the purchase of the allegedly defective materials.